

U.S. Serial No. 10/827,089  
Filed: April 19, 2004  
RESPONSE TO OFFICE ACTION

**Amendments to the Claims:**

1. (Previously presented) A detection system for detecting, locating and classifying an object selected from the group of magnetic and conducting objects, the detection system adapted to detect a secondary magnetic field generated by the object in response to a primary magnetic field transmitted by the detection system, the detection system including an active subsystem for generating an alternating current magnetic field of simultaneous multiple frequencies and a synchronous detection subsystem for accurately measuring the amplitude and phase of the secondary magnetic field;

in which the synchronous detection subsystem includes a plurality of sensors, and the active subsystem is adapted to shape the transmitted field in the vicinity of the sensors in order to reduce the sensors' sensitivity to the transmitted field and to desensitize the sensors to movement with respect to the active subsystem.

Claims 2-4 (Canceled)

5. (Currently amended) Apparatus for determining presence of an object comprising:

a. an emitter adapted to produce and propagate a time varying primary electromagnetic field;

b. at least one sensor, the sensor adapted to receive a secondary electromagnetic field, the secondary electromagnetic field produced by the object as a function of the primary electromagnetic field;

U.S. Serial No. 10/827,089  
Filed: April 19, 2004  
RESPONSE TO OFFICE ACTION

c. the sensor coupled to a receiver, the receiver adapted to determine differences in phase between the primary electromagnetic field and the secondary electromagnetic field and to provide information corresponding to identification of the material forming the object as a function of said phase differences; and

d. in which the primary electromagnetic field contains at least one code and the at least one sensor uses the code of said primary electromagnetic field to determine said phase differences;

e. wherein the at least one sensor is adapted to determine amplitude of the secondary electromagnetic field and to provide information corresponding to distance of the object to the at least one sensor; and

f. wherein [Apparatus according to claim 4 in which] the at least one sensor is adapted to sense gradients in the secondary electromagnetic field.

6. (Currently amended) Apparatus for determining presence of an object, comprising:

a. an emitter adapted to produce and propagate a time varying primary electromagnetic field;

b. at least one sensor, the sensor adapted to receive a secondary electromagnetic field, the secondary electromagnetic field produced by the object as a function of the primary electromagnetic field;

c. the sensor coupled to a receiver, the receiver adapted to determine differences in phase between the primary electromagnetic field and the secondary

U.S. Serial No. 10/827,089  
Filed: April 19, 2004  
RESPONSE TO OFFICE ACTION

electromagnetic field and to provide information corresponding to identification of the material forming the object as a function of said phase differences; and

d. in which the primary electromagnetic field contains at least one code and the at least one sensor uses the code of said primary electromagnetic field to determine said phase differences;

e. wherein the at least one sensor is adapted to determine amplitude of the secondary electromagnetic field and to provide information corresponding to distance of the object to the at least one sensor; and

f. wherein the apparatus comprises [Apparatus according to claim 3 comprising] at least two sensors, the sensors further adapted to sense amplitude and gradients in the secondary electromagnetic field, the sensors further adapted to provide information relating to direction and distance of said object from at least one of said sensors.

Claims 7-11 (Canceled)

12. (Currently amended) Apparatus for determining presence of an object, comprising:

a. an emitter adapted to produce and propagate a time varying primary electromagnetic field;

U.S. Serial No. 10/827,089  
Filed: April 19, 2004  
RESPONSE TO OFFICE ACTION

b. at least one sensor, the sensor adapted to receive a secondary electromagnetic field, the secondary electromagnetic field produced by the object as a function of the primary electromagnetic field;

c. the sensor coupled to a receiver, the receiver adapted to determine differences in phase between the primary electromagnetic field and the secondary electromagnetic field and to provide information corresponding to identification of the material forming the object as a function of said phase differences; [and]

d. wherein the emitter is adapted to pulse width modulate the primary electromagnetic field and

e. wherein [Apparatus according to claim 11 in which] the emitter uses switched capacitors in order to pulse width modulate the primary electromagnetic field.

Claims 13-14 (Canceled)